

SEE WHAT
GLASS
CAN DO
GGI

Patterned Glass

Pattern	Privacy Level	Thickness	Visible Light Transmission	Solar Transmission
Albarino P. Low Iron	High	5/32"	92%	91%
Altdeutsch K	Low	5/32"	90%	87%
Antique	Medium	1/4"	91%	91%
Artico	Medium	1/4"	NPD	NPD
Autumn	High	5/32"	90%	86%
		1/4"	88%	77%
		3/8"	86%	70%
Aqualite	High	3/16"	86%	82%
		1/4"	85%	81%
Bamboo	High	1/4"	87%	77%
		3/8"	84%	69%
Bubbles	High	1/4"	88%	79%
		3/8"	85%	72%
Cast	Medium	1/4"	86%	76%
		3/8"	84%	67%
Chinchilla	High	5/32"	NPD	NPD
Cotswold	High	5/32"	90%	86%
Cross Reeded Small	High	5/32"	NPD	NPD
Delta Frost	High	5/32"	NPD	NPD
Everglade	High	5/32"	90%	86%
		1/4"	88%	77%
Flemish	Low	5/32"	90%	86%
		1/4"	88%	77%
		3/8"	86%	70%
Glue Chip - Double	High	1/4"	NPD	NPD

Consult GGI's Standard Inventory list for available thicknesses

NPD - no performance data

For more information contact marketing@generalglass.com.

Pattern	Privacy Level	Thickness	Visible Light Transmission	Solar Transmission
Glue Chip - Single	Medium	1/4"	NPD	NPD
Master Carre	Medium	5/32"	89%	85%
		1/4"	89%	85%
		3/8"	89%	85%
Master Ligne	Medium	5/32"	89%	85%
		1/4"	88%	83%
Master Point	Medium	5/32"	89%	83%
		1/4"	85%	81%
Master Ray	Medium	5/32"	85%	81%
		1/4"	85%	81%
Monumental - Clear	High	5/32"	89%	85%
Morisco	High	5/32"	NPD	NPD
Rainx (Niagra)	High	1/4"	85%	81%
		3/8"	84%	68%
Reeded	Medium	1/4"	86%	82%
		3/8"	86%	71%
Seedy	Low	1/8"	NPD	NPD
Seedy Marine	Low	1/8"	NPD	NPD
Soft Hammered	Medium	3/8"	NPD	NPD
Stipolite	High	1/8"	89%	85%
		3/16"	87%	83%
		3/8"	83%	69%
Taffeta	Medium	5/32"	90%	77%
Textured Flutes	High	3/16"	NPD	NPD
Thin Ribbed	High	1/4"	NPD	NPD
Water Wave	Low	1/8"	NPD	NPD

NPD - no performance data

Indicative values only. Light will be scattered and diffused due to the pattern on the glass. The values vary based on glass positioning and application. Actual values may vary due to the production process and manufacturing tolerances.

Fabrication

Cutting	Yes
Polishing	Yes
Drilling and notching	Yes
Beveling	Yes
Bending	Yes
Tempering	Yes - Except for 1/8" Antique, Seedy, Seedy Marine
Laminating	Yes - Smooth side, special interlayers may be required
Back painting	Yes - Smooth side
Digital Ceramic Printing	No
Product Availability	Custom fabrication and full case quantities

Product Guidelines

Technical Specification

GGI patterned glass meets or exceeds ASTM C1036 Type II, Class I, Q5

Storage

Glass should be stored vertically in a cool, dry and well ventilated area. If moisture or humidity is detected, separate sheets and dry immediately.

Handling and Care

Use a mild, non-abrasive solution and apply uniformly to the glass surface with a soft cloth. Immediately dry the glass surface with a lint free cloth.

Limited Warranty

GGI warrants to its customers, who shall in turn be able to pass on said warranty to its customers, clients or purchasers that the products supplied shall meet or exceed ASTM standards and be free from workmanship defects for a period of five (5) years from the date of shipment provided that the materials have been stored, handled, installed and maintained according to GGI's instructions and recommendations. For complete warranty please contact GGI.