



# Glass Marker Boards

## Benefits

- Available magnetic or non-magnetic
- Easy to clean, no staining
- No special cleaning agent required
- Non-porous hygienic surface

## Applications

- Classrooms
- Daycare Facilities
- Hospital & Patient Rooms
- Hotel Meeting Rooms
- Offices and Conference Rooms
- Restaurants



## Customization

- Custom shapes
- Custom cut-outs, holes and notches
- Custom color back-painting
- Custom printed designs made easy
  - Company Logo
  - Calendar
  - To-Do Lists
  - Original Artwork
- Simulated chalkboards in green or black



# General Characteristics

Max Sheet Size	Custom Sizes Are Available Minimum: 12" x 12" Maximum: 70" x 144"
Glass thickness	3/16" - 1/4" Single-sided 3/8" - 1/2" Double-sided
Glass types	Clear Ultra-Clear or Low-Iron Crystal Light for a Soft Matte Finish
Options	Single-sided or Double-sided Magnetic or Non-Magnetic
Applications	Interior

## Product Guidelines

### Cleaning

The face of the glass should be cleaned with warm soapy water and a non-abrasive brush or cloth. Do not use cleaning solutions that contain acid alkali or ammonia. Care should be taken to avoid pooling of water at the bottom edge, as this may result in the degradation of the painted surface. This can be easily accomplished by applying the cleaning solution to the cloth, and not directly to the glass marker board.

### Limited Warranty

GGI glass marker boards are produced in accordance with ASTM standards and warranted to be free from workmanship defects for a period of five (5) years from the date of shipment to the original purchaser provided that the materials have been stored, handled, installed and maintained according to GGI's instructions and recommendations. This information is included in this document and online at [www.generalglass.com](http://www.generalglass.com). For complete warranty, please contact GGI.

### Handling and Installation

Glass markerboards should be stored in a dry location at all times and installed in areas that are free from moisture and humidity. **Mounting hardware available upon request.**